


AP-Acoustical Panels

Impact Resistant Wall Panels



The AP Acoustical Panels Provides

- Ideal for use as a general purpose acoustical wall panel where high abuse resistance is not required
- Extensive finish options available in EUROMAT, PRINTS, polyesters, olefins, olyolefins, polypropylenes and Xorel fabrics plus vinyls, and COM

Reflect

Reflect resilient or hardened edges in square, bevel, chamfer, pencil radius, bullnose + customconfigurations

Sustainable Fiberglass Core

- 50% post-consumer recycled glass
- · Manufactured in Shelbyville, IN

LEED Credits

- MR Credit 4.1 = 1 point
- MR Credit 4.2= 1 point
- EA Credit 1= 1 to 10 points
- EQPR3 Prerequisite
- EQ Credit 7.1 = 1 point
- EQ Credit 9 = 1 to 2 points
- EQ Credit 10 = 1 point





Product Data

AP -Acoustical Panels

Specifications

Section 09 83 19 Acoustical Wall Panels

Finish

EUROMAT, PRINTS, polyesters, olefins, polyolefins, polypropylenes and Xorel fabrics plus vinyls, customs and COM

Materials

1" x 6 pcf fiberglass cores are inert, non-combustible, dimensionally stable and fully upholstered with heat sealed corners

Configurations

Flat, curved, flexible

Fire

ASTM E 84 all components are Class A

Corner

Square, radius + custom

Shape

Rectangular + custom

Size

Up to 48" x 120" + custom

Edge

Profile: square, bevel, chamfer, pencil radius, bullnose + custom

Construction: REFLECT resilient standard with optional hardened and aluminum edges

Acoustics

Desciption	hz	125	250	500	1000	2000	4000	NRC
3/4 "		0.10	0.19	0.57	0.97	1.10	1.12	0.70
1 "		0.05	0.33	0.90	0.97	1.10	1.12	0.85
1-1/2"		0.24	0.71	1.10	1.15	1.13	1.08	1.05
2"		0.33	0.71	1.23	1.29	1.22	1.24	1.10

Tested per ASTM C-423 in a type A mounting with unbacked, acoustically transparent panel fabric

Mounting

IMPALIT CLIP, ROTOFAST, z-bar/z-clip, z-clip/z-clip, adhesive, magnetic



Standard EUROMAT Colors

Limitation

AP-ACOUSTICAL panels are not intended for use in harsh environments such as exteriors, kitchens, food processing, food preparation and cleanrooms EUROMAT are not designed for use in the occupied space and should be restricted to wall applications above 10' The use of acrylic backed fabrics will reduce the acoustical performance of the panel









Cove



Peach



Acorn



Dew





Vanilla



Shell





Pale Lemon



Reflection



















Option: color matching to all major paint manufactures, most breathable fabrics, vinyl and complete custom fabric capabilities



204.783.6297

866-525-4496

estimating@soundconceptscan.com

W soundconceptscan.com

599 Henry Avenue, Winnipeg, MB, Canada R3A 0V1